



Skymaster X - 41536

Convertible to take on challenging tasks with greater safety.

Product description

- Can be used on steps/stairs (Order Nos. 41536-41540).
- One rigid locking bar.
- Upper ladder can also be used separately as single ladders for Order Nos. 41536-41540.
- High-strength Perlon straps with sewn-in fixing tab to prevent splaying.
- Optimum wrap-around stile guide that encompasses the whole rung.
- Rung hook and stile guides are bolted in and can therefore be replaced.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.
- Rungs and stiles made from aluminium extrusions.



Product features

Coating: natural
Connection between stiles and rungs/stiles: flanged
Ladder length as 3-part single ladder: 4.1 m
Length as 2-part single ladder and as stepladder with push-on section: 3 m
Load: max. 150 kg
Material: aluminium
Number of rungs: 6
Number of rungs: 3 × 6
Overall length, retracted: 1.9 m
Product type: Flanged multipurpose ladder, 3 sections
Stile depth: 68 mm
Transport dimensions: 1.880 mm × 500 mm × 180 mm
Tread depth: 30 mm
Type of rungs/treads: serrated
Vertical distance between each rung/tread: 265 mm
Weight: 13.8 kg
Wide crosspiece: 0.8 m
Working height as 3-part single ladder: 5 m

Hints and special features

Complies with EN 131 Professional.

Accessories and spare parts

Image	Order number	Name	Type
	40254	Retractable stile extension for multi-section ladders	Accessory
	40255	Retractable stile	Accessory

Image	Order number	Name	Type
	40227	extension for multi-section ladders 3-Part Skymaster™	Parts list