

Skymaster X - 41537

Convertible to take on challenging tasks with greater safety.

Product description

- Can be used on steps/stairs (Order Nos. 41536-41540).
- One rigid locking bar.
- Upper ladder can also be used separately as single ladders for Order Nos. 41536-41540.
- High-strength Perlon straps with sewn-in fixing tab to prevent splaying.
- Optimum wrap-around stile guide that encompasses the whole rung.
- Rung hook and stile guides are bolted in and can therefore be replaced.
- Replaceable 2-component plastic end caps ensure positioning without risk of slipping.
- Rungs and stiles made from aluminium extrusions.



Coating: natural

Connection between stiles and rungs/stiles: flanged

Ladder length as 3-part single ladder: 5 m

Length as 2-part single ladder and as stepladder with

push-on section: 3.6 m Load: max. 150 kg Material: aluminium Number of rungs: 7 Number of rungs: 3 × 7

Overall length, retracted: 2.2 m

Product type: Flanged multipurpose ladder, 3 sections

Stile depth: 68 mm

Transport dimensions: 2.160 mm × 500 mm × 180 mm

Tread depth: 30 mm

Type of rungs/treads: serrated

Vertical distance between each rung/tread: 265 mm

Weight: 15 kg

Wide crosspiece: 0.9 m

Working height as 3-part single ladder: 5.8 m





Hints and special features

Complies with EN 131 Professional.

Accessories and spare parts

Image	Order number	Name	Туре
	40254	Retractable stile extension for multi- section ladders	Accessory
	40255	Retractable stile	Accessory



Image	Order number	Name	Туре
		extension for multi- section ladders	_
	41097	3-Part Skymaster™	Parts list