The World's first mobile telescopic scaffold tower



4.0m of working height & 7 different height options



4 metres of working height

Product Specifications

Code	Includes pack of four toe boards	Material	Platform Height Options (m)	Max. working height (m)	Max. working Incl. railing	Weight (kg)
TT001	No	Alloy	0.33/0.61/1.00/1.25/1.50/1.75/2.00	4.00	4.95	57
TT002	Yes	Alloy	0.33/0.61/1.00/1.25/1.50/1.75/2.00	4.00	4.95	61

Product Footprint

Folded	d Down	Extended		
With Wheels (cms)	Without Wheels (cms)	Stabilisers retracted (cm)	Stabilisers deployed (cm)	
105 (H) x 81 (W) x 42 (D)	83 (H) x 81 (W) x 42 (D)	140 (L) x 75 (W)	184 (L) x 117 (W)	

ORDER YOURS TODAY - FREE DELIVERY

Conforms to EN1004

- Telescopic mechanism allows 7 adjustable platform heights from 0.3m to 2.0m (Working heights from 2.3m to 4.0m)
- Large folding alloy platform (1.4m x 0.7m) with hatch
- Fully erected in under 3 minutes, saving downtime & man hours
- Also available in non-conductive Fibreglass for electrical trades
- Single person operation
- Minimal product footprint for ease of transportation & storage
- Conforms to European Mobile Tower standard : EN1004

Midland Ladder Co. Ltd.

Unit 3, Mere Green Business Village Saltway, Hanbury Worcestershire WR9 7DZ

www.midlandladders.com

email: sales@midlandladders.com

Tel: 01527 821651